





ZION 1500W PORTABLE POWER STATION

Product name Product model

Product model ZION 1500 Product volume 11.81 × 8.46 × 9.76in

Noise volume

Portable Power Station ZION 1500 $11.81\times8.46\times9.76 in$ $(300.0\times215.0\times248.0 mm)$

4 1.0 dB Max

Output power

Battery capacity

Product weight

Working Temperature

1500W

1619Wh

≈33.07lbs (15.00kg)

-10~40 °C (charging)

-20~40 °C (discharging)

CHARGING MODE

- Solar & car output port input: XT60 port (800W max.) and about 2-3 hours for full power.
- **Mains input:** 1 hour to be 80% charged and about 1.67 hours to be fully charged by the bidirectional inverter AC input.

DISPLAY

- **LED function:** Medium lightness high lightness SOS flashing off (5-mode cycle).
- ♦ HMI display: Battery power progress bar, battery power percentage, battery alarm, charging/discharging power, remaining charging/discharging working time, port connection indicator, high/low temperature alarm, overload warning, and fan state.

SUITABLE FOR


















LED light function



Type A USB output port



Type C USB output port



Car charger output port



AC output switch socket

ELECTRICAL

Car output port power AC input PV input

USB-A Output (x2) USB-C Output (x2)

AC Output (x2) AC Output (Bypass) LED Lights 13.2V -- 10A, 132W Max

100V-120V~/60Hz, 1200W Max 10V-46V ---23A, 800W Max

5V =3A/9V =2.6A/12V =2A, 24W Max

5V =3A/9V =3A/12V =3A/15V =3A/20V =5A, (Single port 100W, 2-way share power to Max 130W,

Protocols supported: Apple2.4 A, PPS/PD3.0/PD2.0, QC4+/QC4/QC3.0/QC2.0, AFC, FCP, low-voltage SCP/high-voltage SCP, PE2.0/PE1.1, SFCP)

120V~/60Hz, 1500W Max, Pure sine wave

120V~/60Hz, 1350W Max

3.2W